



**BUTT**  
**05935**

**S3 M HRO SRC**  
**EN ISO 20345:2011**  
**38 to 47**

**Metatarsal protection shoe**  
**Type boot**



## SPECIALS

- Ⓢ Black all purpose sporty ankle boots.
- Ⓢ Water-repellent grained leather upper. Thickness 1.9/2.1mm
- Ⓢ **Metatarsal protection anti-abrasion leather covered** to protect the instep from glass projection. When fixed onto the shoe, it spreads impacts across as wide an area as possible. **(Marked M)**.
- Ⓢ Upper lining in textile Airlight.
- Ⓢ Vamp lined in non-woven textile.
- Ⓢ Padded ergonomic collar with compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Ⓢ Lace up on four pairs of lace stays. Black laces : 120 cm.
- Ⓢ Tongue combined with two side bellows to prevent any dirt from getting into the boots.
- Ⓢ Complete **VENTO PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- Ⓢ **Stainless rustproof steel midsole.**
- Ⓢ **200 Joules safety Stainless rustproof steel toe cap.**
- Ⓢ Antistatic shoe.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water  
and detergent

On flat **0,41** (>0,32) – On the heel **0,32** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,21** (>0,18) – On the heel: **0,16**  
(>0,13)

### Outsole in dual component CA / PU

- ▶ Highly resistant to oils, hydrocarbons and acids at low concentrations.
- ▶ Resistant to direct contact heat up to 300°C.
- ▶ Multi-directional treads and self cleaning sole pattern.
- ▶ Heel shock absorption > 20 Joules.



Weight	Gross weight (42) : 1738 g / Net weight (42) : 1520 g		
Size	38 to 39	40 à 45	46 to 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions (mm)	360 x 255 x 700	360 x 510 x 700	360 x 255 x 700
Dimensions box (mm)	340 x 245 x 133		