



**SHIELD RS  
54614**

**S3 CI HI HRO SRC  
EN ISO 20345:2011  
38 to 47**



**Shoe Type boot**



## **SPECIALS**

- Black all purpose sporty ankle boots.
- Water-repellent grained leather upper. Thickness 1.9/2.1mm
- **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lined in non-woven textile.
- Padded ergonomic collar with compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on four pairs of lace stays and one speed laces. Black laces : 120 cm.
- Tongue combined with two side bellows to prevent any dirt from getting into the boots.
- Shoe with thermal insulation against cold (CI) and heat (HI).
- Complete **VENTO PLUS®** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- Stab-proof non-metallic **FLEX-SYSTEM® zéro** liner : total protection of the sole of the foot.
- **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.
- Antistatic shoe.

### **Slip resistance tests results**

EN Standard : EN ISO 20345 : 2011

#### **Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,42** (>0,32) – On the heel **0,32** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,21** (>0,18) – On the heel: **0,16** (>0,13)

### **Outsole in dual component CA / PU**

- Highly resistant to oils, hydrocarbons and acids at low concentrations.
- Resistant to direct contact heat up to 300°C.
- Multi-directional treads and self cleaning sole pattern.
- Heel shock absorbtion > 20 Joules.



Weight	Gross weight (42) : 1488 g		/ Net weight (42) : 1280 g	
Size	38 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs		10 pairs	
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions	680 x 215 x 350	680 x 425 x 350	685 x 500 x 350	685 x 250 x 350