



**SOLVEX
7AX81**

**S3 SRC
EN ISO 20345:2011
36 to 47**

**High shoe
Urban sport**

SPECIALS



- ⊗ High urban sport safety shoe, black colour. PU toe protection in front.
- ⊗ Wat-Out microfiber upper with resin combines optimal breathability and unmatched watertightness.
- ⊗ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Haut de tige matelassé pour un meilleur confort au niveau des malléoles et du tendon d'achille.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Fastened by lacing through 4 pairs of lace stays. Laces 110 cm 36 to 41 and 120 cm 42 to 47.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ Complete **CONFORT PLUS®** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM®** liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC**
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,44** (>0,32) – On the heel **0,37** (>0,28)

SRB Test ground : steel / lubricant : glycerine
On flat **0,19** (>0,18) – On the heel: **0,15** (>0,13)

W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1250 g / Net weight (42) : 1032 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions box (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350