



**KANYE  
ABI04**

**S3 SRC  
EN ISO 20345:2011  
35 to 48**

**Black sporty urban safety shoes  
Antistatic**

**24 BIT**

**OVERDRY**

**COMFORT  
PLUS**

**ALULITE**

**FLEXsystem  
ZERO**

- ⊗ Black sporty urban safety shoes .
- ⊗ Water-repellent full-grain leather upper, pull-up finish.
- ⊗ Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- ⊗ Vamp lined in non-woven fabric.
- ⊗ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- ⊗ Fluorescent markings for increased visibility when doing night work.
- ⊗ Closure by laces. Laces : 140 cm.
- ⊗ Bellows tongue for superior waterproofing. Padded tongue to protect the top of the foot.
- ⊗ **CONFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- ⊗ **FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ⊗ **ALU-LITE**® 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.

**98GRIP**



**Dual density PU sole** , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

**Slip resistance tests results**  
EN Standard : EN ISO 20345 : 2011  
**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42) : 1460 g / Net Weight (42) : 1158 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs		10 pairs	
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions (mm)	680 x 215 x 350	680 x 425 x 350	685 x 500 x 350	685 x 250 x 350