

VIGOREX

OVERDRY

COMFORT
PLUS

ALULITE*

FLEXsystem
ZERO

- Ⓢ High safety shoe, urban sport type, designed with anti-fatigue technology.
- Ⓢ Leather upper, water resistant, pull-up finish. Color black.
- Ⓢ Upper lined in breathable textile OVER DRY, very resistant and better foot ventilation .
- Ⓢ Vamp lined in non-woven fabric.
- Ⓢ Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- Ⓢ Closure by laces. Laces : 160 cm.
- Ⓢ Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Ⓢ Tabs at the back for easy pull-on.
- Ⓢ **CONFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- Ⓢ **FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- Ⓢ **ALU-LITE**® tip in aluminium resisting an impact of an energy of 200 joules.



Semelle VIGOREX in bi-ingredient PU / and insert in E-TPU
Expanded Thermoplastic PolyUrethane called Infinergy® of BASF

► E-TPU insert at low density of 0.25.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to return energy).

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water
and detergent
On flat **0,77** (>0,32) – On the heel **0,64** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** (>0,18) – On the heel: **0,22** (>0,13)

Weight	Gross Weight (42) : 1390 g / Net Weight (42) : 1182 g			
Size	35 - 39	40 - 41	42 - 45	46 - 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions (mm)	680 x 215 x 350	680 x 425 x 350	685 x 500 x 350	685 x 250 x 350