



**TEUTON ESD
IA209**

S3 CI SRC

EN ISO 20345:2011

35 to 48

**Sporty urban safety shoes
Antistatic**

VIGOREX

OVERDRY

**COMFORT[®]
PLUS**

ALU-LITE[®]

**FLEX[®] system[®]
ZERO**

- ⦿ Low safety shoe, urban type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.
- ⦿ Low safety shoe, urban sport type, designed with anti-fatigue technology.
- ⦿ Leather upper, water resistant, pull-up finish. Color black.
- ⦿ Upper lined in breathable textile OVER DRY, very resistant and better foot ventilation .
- ⦿ Vamp lined in non-woven fabric.
- ⦿ Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- ⦿ Closure by laces. Laces : 120 cm.
- ⦿ Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- ⦿ **CONFORTPLUS[®] ESD** footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- ⦿ **FLEX-SYSTEM[®] ESD** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ⦿ **ALU-LITE[®]** tip in aluminium resisting an impact of an energy of 200 joules.



Semelle VIGOREX in bi-ingredient PU / and insert in E-TPU
Expanded Thermoplastic PolyUrethane called Infinergy[®] of BASF

► E-TPU insert at low density of 0.25.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to return energy).

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water
and detergent

On flat **0,77** (>0,32) – On the heel **0,64** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,30** (>0,18) – On the heel: **0,22**
(>0,13)

Weight	Gross Weight (42) : 1366 g / Net Weight (42) : 1158 g		
Size	35 - 39	40 - 41	42 - 45
Packaging	5 pairs	10 pairs	5 pairs
Box (mm)	306 x 192 x 114	340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350
			680 x 215 x 350