

CONCORDE
7RE05

S3 SRC
EN ISO 20345:2011
38 to 47

Low-ankle Oxford shoe



MANAGER



- Ⓢ Black safety shoe, wing cap, Oxford shoe type..
- Ⓢ Upper in finest quality black water-resistant leather, 1,9 / 2,1 thick.
- Ⓢ Lining in brown **AIR-LIGHT**[®] highly breathable and fast-drying.
- Ⓢ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓢ Padded collar in firm, flexible foam provides extra comfort to the ankle-bones.
- Ⓢ Front lacing over leather tongue.
- Ⓢ **Techfelt** footbed in non-woven fabric.
- Ⓢ Stab-proof non-metallic **FLEX-SYSTEM**[®] liner, protects the entire sole of the foot.
- Ⓢ Steel safety toe-cap offers protection from a 200J impact.

Slip resistance tests results

EN Standard : EN ISO 20345:2011 **Requirement SRC**
(SRA+SRB)

SRA Test ground : ceramic/lubricant water and detergent

On flat : **0,34** (>0,32) - On the heel : **0,30** (>0,28)

SRB Test ground steel/lubricant : glycerine

On flat : **0,19** (>0,18) - On the heel : **0,14** (>0,13)

PU double density sole:

- Scuff-resistant
- Resists oils and hydrocarbons
- System to absorb heel impact

| | | | | |
|------------|---------------------------------------|-----------------|-----------------|-----------------|
| Weight | Brut (42) : 1132 g / Net (42) : 914 g | | | |
| Size | 38 to 39 | 40 to 41 | 42 to 45 | 46 to 47 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box (mm) | 306 x 192 x 114 | | 340 x 210 x 133 | |
| Dimensions | 585 x 199 x 315 | 585 x 395 x 315 | 680 x 425 x 350 | 680 x 215 x 350 |

