SUPERTOUCH®



PRODUCT INFORMATION

Deflector F

Description:

Our Deflector F offers the highest level of cut resistant, which is ideal for a host of tough/sharp handling tasks including warehousing and construction activities.

- ✓ EN 388 levels 4-X-4-3-F
- ✓ Cut level F
- ✓ Enhanced abrasion resistance
- √ Highest level of tear resistance
- ✓ Touch screen
- √Knitted wrist band

Material:

- Nitrile palm coating
- HPPE/Steel/Fibre liner

Applications:

Tasks with maintenance, warehousing, construction, fabrication/assembly, material handling, general plant use, sharp handling

Packaging:

1 pair per Card header - 12 card headers per master poly - 10 master polybags per case

Product Codes:

SPG-27261-5 S - XXL Deflector F

Colourways:



Standards:




EN 388:2016+A1:2018



Abrasion: 4
Blade Cut: X
Tear: 4
Puncture: 3
ISO cut level: F

PPE Regulation (EU) 425/2016 BS EN ISO 21420:2020 - Sizing & Dexterity: PASS BS EN 388:2016+A1:2018 - Protection Against Mechanical Hazards





Size Chart:

Measurements in mm	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)
Hand Length (A)	171	182	192	204	215
Hand Circumference (B)	178	203	229	254	279