



vimeo.com/pyramex/h2max

Capstone 500 Series **ANSI CE CSA BALLISTIC**

Fits over prescription glasses

Soft vinyl goggle body conforms to facial contours

Goggle provides protection against dust and chemical splash

Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance

EGG504T passes D3: Droplet and Splash Test – provides protection from droplets and splashes

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Part No.	Gray Body with Quick Release Strap
EGG504T ●●●●	AF Clear H2X

General Specifications

Weight: 92 gm
PD: 68 mm
Bridge: 45 mm
Lens base: 5.5 curve
Lens size diagonal: 154 mm
Lens size vertical: 78 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 91 mm
Overall width (hinge - hinge): 180 mm
Strap length: 540 mm

Materials

Lens: polycarbonate
Body: polycarbonate & polyvinyl chloride (PVC)
Headband: textile elastic
Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
EGG504T	2C - 1.2 P 1 BT N CE	CE P EN166 3 4 BT

Lens Marking Symbols

Code - field of use

2 or 3: UV filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s

T: Additional resistance at extreme temperatures

Symbols

P: Manufacturer's mark

N: Filter with anti-fog

CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard

P: Manufacturer's mark

EN166: CE specification for protective eyewear

3: Liquid droplets and splash

4: Large dust particles

Mechanical Strength

B: High speed particles with medium energy impact

T: Additional resistance at extreme temperatures

There's more to see at
PYRAMEXSAFETY.COM

[P] +44 (0) 1635 254220 | [E] info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●), Canadian [CSA Z94.3] (●) or Ballistic [MIL-PRF-32432] (●) standards. For specific lens options visit our website or contact your sales representative.