

**Neshoba™ is one of the lightest weight spectacles on the market, weighing in at 16 grams.** To eliminate the threats of an eye injury, an employer should provide workers with products that are comfortable and dependable.







**Neshoba™** ANSI • CE • CSA •

Frameless design with thin flexible temples // Ultra lightweight spectacle – 16 gm

**Black Temples | 7 Variations**

	ES9710S ●●●	Clear
	ES9710ST ●●●	Clear <b>H2X</b> AF
	ES9720S ●●●	Gray
	ES9720ST ●●●	Gray <b>H2X</b> AF
	ES9730S ●●●	Amber
	ES9780S ●●●	I/O Mirror
	ES9780ST ●●●	I/O Mirror AF

**Black Temples with Cord | 4 Variations**

	ES9710SP ●●●	Clear
	ES9710STP ●●●	Clear <b>H2X</b> AF
	ES9720SP ●●●	Gray
	ES9780SP ●●●	I/O Mirror



**There's more to see at**  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●) or Canadian CSA Z94.3 (●) standards. For specific lens options visit our website or contact your sales representative.

## Neshoba™

### General Specifications

Weight: 16 gm  
 PD: 64 mm  
 Bridge: 12.3 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 75.8 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.6 mm  
 Overall length (lens - tip): 151 mm  
 Overall width (hinge - hinge): 135 mm  
 Closest point between temple tips: 78 mm  
 Closest point between lens: 14.5 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate  
 Hinge: polycarbonate  
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
ES9710S	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710SP	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710ST	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9710STP	2 C - 1.2 P 1 F CE	CE P EN166 F
ES9720S	5 - 2.5 P 1 F CE	CE P EN166 F
ES9720SP	5 - 2.5 P 1 F CE	CE P EN166 F
ES9720ST	5 - 2.5 P 1 F CE	CE P EN166 F
ES9730S	2 - 1.2 P 1 F CE	CE P EN166 F
ES9780S	5 - 1.7 P 1 F CE	CE P EN166 F
ES9780SP	5 - 1.7 P 1 F CE	CE P EN166 F
ES9780ST	5 - 1.7 P 1 F CE	CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Color perception

C: Unimpaired color perception

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 CE: Europe standard

### Frame Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com